



UKC2+H

Unit No.	Shaft Dia.		Dimensions (mm) (inch)				Bearing No.	Housing No.	Adapter Used.	Weight (kg) (lb)
	d		L	A	r	B ₁				
	(in.)	(mm)								
UKC205+H2305		20	80	22	2.0	35	UK205	C205	H2305	0.68
UKC205+HE2305	$\frac{3}{4}$		3.1496	0.8661	0.0787	1.3780			HE2305	1.5
UKC206+H2306		25	85	27	2.0	38	UK206	C206	H2306	0.89
UKC206+HS2306	$\frac{7}{8}$								HS2306	
UKC206+HA2306	$1\frac{15}{16}$		3.3464	1.0630	0.0787	1.4961			HA2306	2.0
UKC206+HE2306	1								HE2306	
UKC207+H2307		30	90	28	2.0	43	UK207	C207	H2307	0.96
UKC207+HS2307	$1\frac{1}{8}$								HS2307	2.1
UKC207+HA2307	$1\frac{3}{16}$		3.5433	1.1024	0.0787	1.6929			HA2307	
UKC208+H2308		35	100	30	2.5	46	UK208	C208	H2308	1.24
UKC208+HE2308	$1\frac{1}{4}$		3.9370	1.1811	0.0984	1.8110			HE2308	2.7
UKC208+HS2308	$1\frac{3}{8}$								HS2308	
UKC209+H2309		40	110	31	2.5	50	UK209	C209	H2309	1.58
UKC209+HA2309	$1\frac{7}{16}$								HA2309	
UKC209+HE2309	$1\frac{1}{2}$		4.3307	1.2205	0.0984	1.9685			HE2309	2.5
UKC209+HS2309	$1\frac{5}{8}$								HS2309	
UKC210+H2310		45	120	33	2.5	55	UK210	C210	H2310	2.04
UKC210+HA2310	$1\frac{11}{16}$		4.7244	1.2992	0.0984	2.1654			HA2310	4.5
UKC210+HE2310	$1\frac{3}{4}$								HE2310	
UKC211+H2311		50	125	35	2.5	59	UK211	C211	H2311	2.30
UKC211+HS2311	$1\frac{7}{8}$								HS2311	
UKC211+HA2311	$1\frac{9}{16}$		4.9212	1.3780	0.0984	2.3228			HA2311	5.1
UKC211+HE2311	2								HE2311	
UKC212+H2312		55	130	38	2.5	62	UK212	C212	H 2312	2.51
UKC212+HS2312	$2\frac{1}{8}$		5.1181	1.4961	0.0984	2.4409			HS2312	5.5
UKC213+H2313		60	140	40	3.0	65	UK213	C213	H2313	3.04
UKC213+HA2313	$2\frac{3}{16}$								HA2313	
UKC213+HE2313	$2\frac{1}{4}$		5.5118	1.5748	0.1181	2.5590			HE2313	6.7
UKC213+HS2313	$2\frac{3}{8}$								HS2313	

Alternative dimensions are available, for critical engineering or construction requirements please confirm these dimensions with your local Ringball branch